

TECHNICAL SPECIFICATIONS:

Model		IL-500	IL-1000	IL-1500	IL-2000	IL-3000	IL-6000
Capacity	W	350W	700W	1050W	1400W	2100W	4200W
Input	Phase	Single					
	Voltage	140-280Vac					
	Frequency	60/50+/-10%					
Output	Phase	Single					
	Voltage range(V ac)	220+/-10%					
	Frequency	50/60+/-0.5Hz					
	Waveform	Sine wave					
Battery	DC Voltage	DC12V	DC12V/24V	DC24V	DC36V/48V	DC48V/96V	DC96V
	Recharge current	Long back up model: 12A max,					
	Transfer Time	Typical: 6ms (Including detection time)					
Display	LCD/LED	Optional					
Protection	Full Protection	Discharge, overcharge, and overload protection etc...					
Physical	Dimension, DxWxH	360*120*185mm		450*145*215mm	385*140*218mm		430*195*160mm
	Net Weight)	7.00kg	10.00kg	15.00kg	19.00kg	21.00kg	45.00kg
Environment	Operating Environment	0~40 Degrees Centigrade, 0~90% relative humidity (non-condensing)					
	Noise Level	Less than 40dB					
Interface	Smart RS-232	Support Windows family, Linux, Compaq True64,					